



Technical Description – AEN-219

| | |
|---|---|
| STYLE | AEN-219 |
| ARTICLE - sizes - colour - weight per pair | DERBY SHOE, perforation on sides Certified to EN 61340-5-1. 35-47 black 800 gr |
| SOLE - anti-slip resistance 0.26 | Polyurethane mono density injected antistatic sole, oil and acid resistant, anti-slip, production date |
| UPPER - tear strength - water vapour permeability - coefficient | “TEXFIBER” material of high perspiration Double stitching 62 N 2,1 mg/cm ² h 19,9 mg/cm ² |
| COLLAR PADDING | Sponge |
| STROEBEL | Woven-unwoven fabric, natural colour |
| COUNTER LINING | fabric lining of excellent transpiration, yellow colour, comfortable and resistant |
| VAMP LINING | Woven-unwoven felt, high sweat absorption |
| INSOLE | ESD insole in soft latex and woven-unwoven fabric |
| TONGUE | Perforated sponge padded “TEXFIBER” of high perspiration |
| COUNTER | Preformed, Thermoplastic, comfortable heel protection and support |
| LACES | Special flat laces for safety footwear, white/grey |
| CLOSING SYSTEM | 5 pairs of plastic eyelets with protection against dirty |
| TOECAP | Synthetic non-magnetic toe cap resistant to 200 J to EN ISO 20345:2004-S1 - elastic return |
| TOECAP PADDING | Woven-unwoven of synthetic latex |
| MARKING | EN ISO 20345:2004-S1 Safe Way label on tongue – ESD flag on upper |
| PACKAGING | Ecological paper, 1 pair 10 pairs/size/carton |

10 Enterprise Drive
 Carbondale, PA 18407, USA
 Tel: (570) 842-2812 Fax: (570) 842-4290
 E-Mail: bokar@bomir.com
 www.bokar.com & www.xkar.com

